

Antiskid Powder

Code: 6530.005

SPECIALLY GRANULATED ADDITIVE FOR ENAMEL PAINTS

- NON ABRASIVE
- EASY TO USE
- CAN BE SPRAYED
- EXCELLENT RESISTANCE TO ABRASION

CHARACTERISTICS

A specially granulated powder of an odourless plastic material for use as an antiskid additive to boat flooring and/or deck paints. It possesses excellent mechanical characteristics and resistance to the marine environment.

TECNICAL DATA

| | |
|-------------------|------------------|
| Curing mechanism: | / |
| Specific weight: | 0,30 ± 0,02 Kg/L |
| Solid By Volume: | 100 % |
| Flash Point: | / |
| Appearance: | / |
| Colour: | / |
| Packaging: | 150 grams |

SURFACE PREPARATION

Depending on requirements, pour in between 4% and 5% by volume to the enamel paint to which the hardener has already been added. Stir carefully before and during application.

APPLICATION

The addition of 4-5% powder by volume to the previously prepared paint generally allows two coats to be applied giving excellent performance and a pleasing appearance. Stir the paint containing the additive frequently as the granules tend to float. Always apply 2 coats. Some 3 to 5 litres of antiskid paint ready for use can be obtained using the 150 g. can.

Antiskid Powder

Code: 6530.005

SPECIALLY GRANULATED ADDITIVE FOR ENAMEL PAINTS

APPLICATION DATA

Drying time before use (20 °C): /
 Pot Life (20 °C): /
 Application temp. min/ max: /
 Hardener: /
 Mixing ratio by volume: /
 Mixing ratio by weight: /
 Thinner/Thinner for cleaning: /
 Wet film thickness per coat: /
 Dry film thickness per coat: /
 Theoretical coverage per coat: /
 Minimum covering time (20 °C): /
 Maximum covering time (20 °C): /
 Number of coats: /

NOTES

| | | |
|--|--|--|
| | | |
| | | |
| | | |
| | | |

SAFETY RULES

Keep out of the reach of children. Do not inhale the powder. Avoid the build-up of electrostatic charges. The product does not require EEC labelling. Before use read the sections 7-8 of the Safety Data Sheet (MSDS).
INSTRUCTIONS FOR THE SAFE BIOCIDAL PRODUCT DISPOSAL AND PACKAGING
 Empty packaging having contained biocidal products: empty packaging shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre.
 Packaging containing unused biocidal product: the unused product shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre, in this case it is forbidden to recycle packaging. Do not empty into drains and watercourses. The paint cans must not be stocked outside and must be stored at a temperature between 10 ° C and 35 ° C. Do not expose to the sun.

DISCLAIMER The information in this data sheet is based on accurate laboratory tests and practical experience, which guarantee the quality of the product if used according to our recommendations. The data contained herein are liable to modification as a result of continuous product development. We do not accept any liability arising from use not in accordance with our recommendations, unless authorized specifically by the Veneziani Technical Services. This edition annuls and replaces all previous issues.