

Fibrodur

Code: 6790....

SEALING PRIMER FOR WOOD

- DEEP PENETRATION
- HIGH STRENGTH TWO-PACK PRODUCT
- PROTECTS AND SEALS

CHARACTERISTICS

A two-pack polyurethane primer for wood with excellent sealing properties. It's deep penetration makes the surface highly impermeable and hard. This product is recommended for use mainly on new or stripped wood. When correctly applied in a single coat it does not form a film but penetrates into the surface. In colourless version it does not alter the original colour of the wood and does not yellow with age. This product can be painted over with a wide range of products such as Eurogel, Epoway, Resina 2000, Ticoprene , Timber Gloss, Wood Gloss and Wood Mat.

TECNICAL DATA

Curing mechanism:	thinner evaporation and chemical reaction
Specific weight:	0.98 ± 0,02 Kg/L
Solid By Volume:	25 %
Flash Point:	+5 °C
Appearance:	semiglossy
Colour:	clear, mahogany, nut-brown, teak
Packaging:	0,75 litres

SURFACE PREPARATION

New wood: apply directly to the bare wood which must be cleaned and then lightly sanded.
Old wood: remove all the old paint using a stripper, a burner, a scraper or abrasive paper.

APPLICATION

Spread the product using a soft brush in order to impregnate and soak the wood fibres. Sand the surface with 180 grade abrasive paper before continuing with the finishing coats. The product is very fluid and does not need thinning.

Fibrodur

Code: 6790....

SEALING PRIMER FOR WOOD

APPLICATION DATA

Drying time before use (20 °C):	3 days
Pot Life (20 °C):	4 hours
Application temp. min/ max:	+5/+35 °C
Hardener:	6790.999
Mixing ratio by volume:	2:1
Mixing ratio by weight:	62:38
Thinner/Thinner for cleaning:	6780 for cleaning only
Wet film thickness per coat:	80 µ
Dry film thickness per coat:	20 µ
Theoretical coverage per coat:	12,5 m ² /L
Minimum covering time (20 °C):	12 hours
Maximum covering time (20 °C):	48 hours
Number of coats:	1-2

NOTES

SAFETY RULES

Adequate ventilation must be provided when applying this product in a confined area and during the subsequent drying period. The product contains solvents which could form an explosive mixture when combined with air and exposed to a naked flame, spark or electrostatic discharge. The use of goggles, masks, gloves and protective clothing is recommended. Before use read the sections 7-8 of the Safety Data Sheet (MSDS).
INSTRUCTIONS FOR THE SAFE BIOCIDAL PRODUCT DISPOSAL AND PACKAGING
 Empty packaging having contained biocidal products: empty packaging shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre.
 Packaging containing unused biocidal product: the unused product shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre, in this case it is forbidden to recycle packaging. Do not empty into drains and watercourses. The paint cans must not be stocked outside and must be stored at a temperature between 10 ° C and 35 ° C. Do not expose to the sun.

DISCLAIMER The information in this data sheet is based on accurate laboratory tests and practical experience, which guarantee the quality of the product if used according to our recommendations. The data contained herein are liable to modification as a result of continuous product development. We do not accept any liability arising from use not in accordance with our recommendations, unless authorized specifically by the Veneziani Technical Services. This edition annuls and replaces all previous issues.