

Microsilice

Code: 6330.005

COLLOIDAL MICROSILICA

- SUITABLE TO PRODUCE COMPOUNDS FOR:
- GLUING OF ACCESSORIES
- LAMINATIONS
- JOINTING

CHARACTERISTICS

MICROSILICE belongs to the range of additives to be mixed with RESINA 2000 in order to produce compounds with different properties. MICROSILICE is a thickening additive used with RESINA 2000. Best suited for gluing, jointing and the repair of defective spots. It may be mixed together with other additives of the range in order to improve knife application and appearance of the product and is suitable for both above and below waterline applications.

TECNICAL DATA

Curing mechanism:	/
Specific weight:	/
Solid By Volume:	/
Flash Point:	/
Appearance:	/
Colour:	/
Packaging:	0,75 litres

SURFACE PREPARATION

Before applying Resina 2000, the surface must be completely dry and clean. Wooden surfaces must be dry and clean, as well as free from grease and oil. The areas to be treated should be sandpapered at first.

APPLICATION

MICROSILICE shall be added to RESINA 2000 only after component A has been mixed thoroughly with component B with a ratio of 2:1.

Gluing and lamination

Mix 2 parts of already catalysed Resina 2000 + 1 part of Microsilice, in order to produce a liquid compound suitable for gluing of small parts and laminations.

Jointing, filling, gluing of accessories

Mix 1 part of already catalysed Resina 2000 + 1 part of Microsilice, in order to produce a paste suitable for jointing, gluing of accessories and as an all purpose filler.

Extensive filling and jointing

Mix 1 part of already catalysed Resina 2000 + 2 parts of Microsilice, in order to produce a structural compound suitable for extensive jointing and filler application.

Microsilice

Code: 6330.005

COLLOIDAL MICROSILICA

APPLICATION DATA

Drying time before use (20 °C): /
 Pot Life (20 °C): /
 Application temp. min/ max: +5/+35 °C
 Hardener: /
 Mixing ratio by volume: /
 Mixing ratio by weight: /
 Thinner/Thinner for cleaning: /
 Wet film thickness per coat: /
 Dry film thickness per coat: /
 Theoretical coverage per coat: /
 Minimum covering time (20 °C): /
 Maximum covering time (20 °C): /
 Number of coats: /

NOTES

SAFETY RULES

The product does not contain dangerous components in conformity with the rules of the EEC, should be used with the usual working precautions and not dispersed into the environment. Keep out of reach of children. Before use read the sections 7-8 of the Safety Data Sheet (MSDS).
INSTRUCTIONS FOR THE SAFE BIOCIDAL PRODUCT DISPOSAL AND PACKAGING
 Empty packaging having contained biocidal products: empty packaging shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre.
 Packaging containing unused biocidal product: the unused product shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre, in this case it is forbidden to recycle packaging. Do not empty into drains and watercourses. The paint cans must not be stocked outside and must be stored at a temperature between 10 ° C and 35 ° C. Do not expose to the sun.

DISCLAIMER The information in this data sheet is based on accurate laboratory tests and practical experience, which guarantee the quality of the product if used according to our recommendations. The data contained herein are liable to modification as a result of continuous product development. We do not accept any liability arising from use not in accordance with our recommendations, unless authorized specifically by the Veneziani Technical Services. This edition annuls and replaces all previous issues.